NSN 5305-00-276-2134

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-276-2134



| Thread Class: |
|--|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.214 inches and 0.250 inches |
| Fastener Length: |
| Between 0.219 inches and 0.250 inches |
| Head Style: |
| Round |
| Head Diameter: |
| Between 0.169 inches and 0.187 inches |
| Head Height: |
| 0.078 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.099 inches |
| Thready Qty Per Inch (tpi): |
| 56 |
| Min. Tensile Strength (psi): |
| 55000 pounds per square inch |
| Screw Material: |
| Steel or steel comp 1010 |
| Screw Material Specification: |
| Qq-s-630 federal specification 2nd material response or qq-s-631 federal specification 2nd material response or qq-s-634 federal |
| specification 2nd material response |
| Screw Surface Treatment: |
| Cadmium |
| Screw Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A500d0 |