NSN 5305-00-276-3067

Shoulder Screw - Page 1 of 1



Group

View Online at https://aerobasegroup.com/nsn/5305-00-276-3067

Thread Class: 2a Thread Direction: Right-hand Thread Longth: Between 0.155 inches and 0.170 inches Fasiener Length: Between 0.237 inches and 0.243 inches Head Sigvic: Falinater Between 0.237 inches and 0.130 inches Head Height: 0.037 inches Between 0.186 inches and 0.190 inches Head Height: 0.037 inches 0.037 inches Shoulder Diameter: 0.037 inches 0.037 inches Shoulder Length: 0.037 inches 0.037 inches 0.038 inches first shoulder Shoulder Length: 0.039 inches 0.039 inches Thread Vall Portich (tpl): Stot Thread Vall Portich (tpl): Stot Shoulder Shape: Navao first shoulder Product Name: Corper alloy 200 or copper alloy 260 or copper alloy 260 or copper alloy 351 or copper alloy 355 or copper alloy 355 or copper alloy 355 or copper alloy 355 or copper alloy 350 or copper alloy 351 or copper	
Firsteline Firsteline Between 0.159 inches and 0.170 inches Fastener Length: Between 0.237 inches and 0.243 inches Head Syle: Fillater Between 0.168 inches and 0.243 inches Head Syle: Other Descent Descen	
Right-hand Fractal Langht: Between 0.155 inches and 0.170 inches Fatteer Catter Between 0.257 inches and 0.243 inches Hand Sayle: Fatteer Catter Between 0.155 inches and 0.243 inches Hand Sayle: Fatteer Catter Between 0.156 inches and 0.190 inches Between 0.156 inches and 0.190 inches Between 0.156 inches and 0.190 inches Boulder Dameter: 0.031 inches 10.34 inches and 0.136 inches first shoulder Shoulder Langht: 10.134 inches and 0.136 inches first shoulder Broter 10.134 inches and 0.136 inches first shoulder Broter Shoulder 100 Fatter Catter 10.134 inches and 0.136 inches first shoulder 10.134 inches and 0.136 inches first shoulder 10.134 inches	
Fread Lengt: Breaken J. 155 inches and 0.170 inches Fausen Lengt: Breaken J. 253 inches and 0.243 inches Had Style: Filles Had Style: Breaken J. 253 inches and 0.190 inches Had Height: 0.181 inches and 0.190 inches Had Height: 0.131 inches and 0.190 inches 194 inches and 0.190 inches 194 inches and 0.180 inches first shoulder 194 inches and 0.181 inches first shoulder 194 inches and 0.81 inches first shoulder 194 incher 194 inches and 0.81 inches first shoulder 194 incher 194 incher <	
Pater Longth: Pater Longth: Reader 0.237 inches and 0.243 inches Head Syle: Filister Filister Pater 0.138 inches and 0.190 inches Head Viet Ox37 inches Ox38 inches first shoulder Ox47 inches and 0.138 inches first shoulder Ox47 inches and 0.038 inches first shoulder Ox47 inches Ox47 inches Ox40 inches	
Fasteer Langth: Retwoen 0.237 inches and 0.243 inches Head Style: Fillister Fasteer 0.186 inches and 0.190 inches Retwoen 0.186 inches and 0.190 inches Head Mainter: 0.203 inches 0.134 inches and 0.136 inches first shoulder Shoulder Langth: 0.134 inches and 0.036 inches first shoulder 7 Shoulder Langth: 0.170 inches and 0.038 inches first shoulder 1047 inches and 0.038 inches first shoulder 1047 inches and 0.038 inches first shoulder 1047 inches 1048 inches 1049 inches 1049 inches 1040 inches 1050 1060 1070 inches 1080 1090 inches 1000 inches	
Patewan 0.293 inches and 0.293 inches Filtar Filtar Pateo Diameter: Bouter Diameter: 0.134 inches and 0.130 inches first shoulder Diameter: 0.134 inches and 0.100 inches first shoulder Diameter: 0.134 inches and 0.083 inches first shoulder Diameter: 0.134 inches and 0.083 inches first shoulder Patema Dire Style: 0.090 inches 104 inches 1050 Patema Dire Style: 0.090 inches 1040 inches 1050 Patema Dire Style: 1050 1060 1071 inches and 0.083 inches first shoulder 1072 inches 1073 inches 1080 inches 1080 inches 1080 inches 1090 inches 1090 inches 1090 inches 1000 inches <t< td=""><td></td></t<>	
Had Style: Filister Filister Battometr: Battom and 0.190 inches Had Hadght: Battom and 0.190 inches Battom ande Battom	
Filiater Filiater Read Charter: 0.307 inches 1.314 inches and 0.190 inches 1.324 inches	
Particle	
Between 0.186 inches and 0.190 inches Head Height: 0.307 inches Shulder Diameter: 0.136 inches and 0.196 inches first shoulder Shoulder Length: 0.077 inches 10.077 inches and 0.083 inches first shoulder Intrend Drive Style: 10.077 inches 10.078 inches 10.018 inst shoulder 10.028 inches 10.018 inst shoulder 10.018 inst shoulder 10.018 inst shoulder 10.020 on copper alloy 20 on copper alloy 200	
Had Height: 0.037 inches 0.041 inches Volder Langett: 0.077 inches 0.078 inches first shoulder 0.077 inches 0.078 inches first shoulder 1.007 inches 0.078 inches 1.077 inches 0.078 inches 1.078 inches 1.078 inches 1.079 inches 1.079 inches 1.099 inches 1.090 inches 1.090 inches 1.091 inc	
0.037 inches 0.134 inches 0.134 inches 0.134 inches 0.134 inches 0.037 inches 0.037 inches 0.038 inches first shoulder Internal Drive Style: 0.039 inches 1000 inches 0.039 inches 1000 inches	
Shoulder Diameter: 0:134 inches and 0.136 inches first shoulder Shoulder Length: 0.077 inches and 0.083 inches first shoulder Interal Drive Style: Stord Thread Diameter: 0.099 inches 1000 inches Pready Qty Per Inch (tpl): 56 Shoulder Shape: Round first shoulder Product Name: Navy special project Material Copper alloy 200 or copper alloy 260 or copper alloy 265 or copper alloy 342 or copper alloy 353 or copper alloy 377 Tread Series Designator: Inf Mari Coper alloy 270. Ford Measure: Inf Inf Infe: Information:	
 1.134 inches and 0.136 inches first shoulder Shoulder Length: 1.077 inches and 0.083 inches first shoulder Iternal Drive Style: Slot Thread Diameter: 0.099 inches Thready Qty Per Inch (tpi): 36 Shoulder Shape: Round first shoulder Product Name: Navy special project Material: Copper alloy 230 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 260 Thread Steles Designator: Inf Inf Inf Inf Inf Inf Inf Inf Inf Inf	
Shoulder Length: 0.077 inches and 0.083 inches first shoulder Internal Drive Style: Stot Thread Diameter: 0.099 inches Thread Vig VP rinch (tpi): 56 Product Shape: Round first shoulder Product Shape: Round first shoulder Product Name: Opper alloy 200 or copper alloy 240 or copper alloy 260 or copper alloy 342 or copper alloy 353 or copper alloy 363 or copper alloy 37 Thread Series Designator: Inf Inf <td></td>	
0.077 inches and 0.083 inches first shoulder Internal Drive Style: Slot Slot Thread Diameter: 0.099 inches Thready Qty Per Inch (tpi): 56 Found first shoulder Pound first shoulder Pound first shoulder Pound Sauge copper alloy 240 or copper alloy 260 or copper alloy 342 or copper alloy 353 or copper alloy 363 or copper alloy 370 Pound Sauge copper alloy 370 Pound first shoulder Pound Sauge copper alloy 371 Pound first shoulder Pound Sauge copper alloy 372 Pound first shoulder Pound Sauge copper alloy 373 Pound first sho	
Internal Drive Style:SlotInteract Diameter:0.099 inchesInteract Quy Per Inch (tpi):SdoSolder Shape:Round first shoulderProduct Name:Navy special projectMaterial:Copper alloy 230 or copper alloy 260 or copper alloy 265 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 266 or copper alloy 342 or copper alloy 353 or copper alloy 360InfPriced Series Designator:InfInfPriced Series Designator:InfPriced Series Designator:InfInfFig:Inf Series Designator:InfInf Series Designator:Inf Series Designator: <td< td=""><td></td></td<>	
Slot Inread Diameter: 0.099 inches Inready Oty Per Inch (tpi): 56 Shoulder Shape: Round first shoulder Product Name: Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Inread Series Designator: Inf Sheft Life: Nav Inf of Measure: Int of Measure: Int of Measure: Int Int of Measure: Int Int of Measure: Int Int of Measure: Int of Measure: Int Int of Measure: Intertization: Intertization: Intertization: Intertization: Intertization: Intertization: Intertization: Intertization: Int of Measure	
Interact Diameter:0.099 inchesInteracty Qty Per Inch (tpi):56Shoulder Shape:Round first shoulderProduct Name:Navy special projectMaterial:Copper alloy 230 or copper alloy 240 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360Or pare alloy 377Interact Series Designator:ViriNavProduct Name:Interact Series Designator:Interact Series Designator:Interact Series Designator:Interact Series Designator:NaInteract Series Designator:Interact Series Designator:	
0.099 inches Inready Qty Per Inch (tpi): 56 Shoulder Shape: Round first shoulder Product Name: Navy special project Matrial: Opper alloy 230 or copper alloy 240 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Inread Series Designator: Nav Nav Inf: Nav Inf: Inf: <t< td=""><td></td></t<>	
Fready Qty Per Inch (tpi): 56 Foulder Shape: Round first shoulder Product Name: Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 342 or copper alloy 353 or copper alloy 363 Proted Series Designator: Unf Sheft Life: Navi Prote Measure: Image: Pointiarization: Na Fig:	
56 Shoulder Shape: Round first shoulder Product Name: Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 342 or copper alloy 353 or copper alloy 370 Proted Series Designator: Unf Shoft Life: Nav Int of Measure: Image: Pointilarization: Na Fig:	
Shoulder Shape: Round first shoulder Product Name: Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Thread Series Designator: Unf Shelf Life: N/a Dirt Of Measure: - Dirt Of Measure: Na Fig:	
Round first shoulder Product Name: Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Thread Series Designator: Unf Sheft Life: Na Di tof Measure: Penilitarization: No Fig:	
Product Name: Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 363 or copper alloy 364 or copper a	
Navy special project Material: Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Material: Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Thread Series Designator: Unf Shelf Life: N/a Uni Of Measure: - Demilitarization: No Fig:	
Copper alloy 230 or copper alloy 240 or copper alloy 260 or copper alloy 268 or copper alloy 342 or copper alloy 353 or copper alloy 360 or copper alloy 377 Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
or copper alloy 377 Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Thread Series Designator: Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Unf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Filg:	
Unit Of Measure: Demilitarization: No Fiig:	
 Demilitarization: No Fiig:	
No Filg:	Unit Of Measure:
No Filg:	
Fiig:	
A003b0	
	A003b0