## NSN 5305-00-276-9661



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-276-9661 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.125 inches **Fastener Length:** 0.125 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.105 inches and 0.119 inches **Head Height:** Between 0.026 inches and 0.035 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.060 inches Thready Qty Per Inch (tpi): 80 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 81.0 degrees and 83.0 degrees **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-f-495 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-00-276-9661

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-495 spec.