## NSN 5305-00-279-9068

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-279-9068

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.314 inches and 0.364 inches
Fastener Length:
Between 0.886 inches and 0.916 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.339 inches and 0.381 inches
Grip Diameter:
Between 0.1890 inches and 0.1895 inches
Internal Drive Style:
High-torque
Thread Diameter:
0.190 inches
Grip Length:
Between 0.552 inches and 0.572 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Titanium alloy
Material Specification:
Nas 621, 6al-4v assn standard 1st material response or ams 4928 assn standard 2nd material response
Thread Series Designator:
Unjf
Specification Data:
80205-nas663 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-00-279-9068

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0