Hexagon Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-00-281-3365



2a Thread Direction: Right-hand Thread Length: 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Head Style: Head Style: Head Height: Between 0.226 inches and 0.243 inches Witht Between 7Lats: Between 0.251 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Thread Vaty Per Inch (tpi): 16 Min Tensile Strength (psi): 80000 pounds per square inch Material: Stel comp 302 or stele comp 303 or stele comp 304 or stele comp 305 or stele comp 304 Material Specification: 61 federal standard all material responses Surface Treatment: Passivat Surface Treatment: Passivat Material: Passivat Material: Passivat Material: Passivat Material: Passivat Material: Passivat Passivat Material: Passivat Material: Passivat Passivat Material: Passivat Passivat Material: Passivat P	Thread Class:
Thread Direction: Right-hand Thread Length: 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Head Style: Head Style: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Fatures Provided: Finished head Thready Qty Per Inch (tpi): 16 Mitn-Basile Strength (psi): 8000 pounds per square inch Material: Stel comp 302 or stel comp 303 or stel comp 304 or stel comp 305 or stel comp 305 Material: Stel comp 302 or stel comp 303 or stel comp 304 or stel comp 305 or stel comp 304 Stel comp 302 or stel comp 303 or stel comp 304 or stel comp 305 or stel comp 305 Straface Treatment: Passivate Chried Streigh Designator: It or desires Designator: <	
Right-hand Thread Length: 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Head Style: Head Style: Between 0.219 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.262 inches Thread Diameter: 0.375 inches Fatures Provided: Finished head Thready Qty Per Inch (tpi): 16 Mith Tensile Strength (psi): 8toteon 302 or steel comp 303 or steel comp 305 or steel comp 305 Material: Sterler Strength (psi): 8toteon 302 or steel comp 303 or steel comp 305 or steel comp 305 or steel comp 305 Strafee Treatment: Passivate Chrider Ispecification: Qu-p-35 federal specification single treatment response Thread Stries Designato:: Iva Materia: Via Chride Hister: Iva Striet Teatment Specification: Iva Striet Teatment Specification: Iva Iva <td></td>	
Pread Length: 0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Head Style: Head Meight: Between 0.226 inches and 0.243 inches With Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 301 61 federal standard all material responses Surface Treatment Specification: Quep-35 federal specification single treatment response Thread Series Designator: Iva Shelf Life: Na Life: Na Dit Of Measure: Iva Fig:	
0.750 inches Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Fastures Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 305 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment Specification: Qap-35 federal specification: Qap-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit of Measure: - Demilitarization: Final Specification: N/a Hord Series Designato: Final Specification: Steel comp Series Desingato: <td>-</td>	-
Fastener Length: Between 0.719 inches and 0.750 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Vidth Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Fatures Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Stele comp 302 or stele comp 303 or stele comp 304 or stele comp 305 or stele comp 305 Stele comp 302 or stele comp 303 or stele comp 304 or stele comp 305 or stele comp 305 Stardard all material responses Surface Treatment: Passivate Ques Stafe deral specification: (acp-35 federal specification single treatment response Thread Steines Designator: Inc Na Linc Na Steled real specification single treatment response Thread Steines Designator: Inc Steled real specification single treatment response Thread Steine	-
Between 0.7 9 inches and 0.750 inches Head Style: Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 6 federal standard all material responses Surface Treatment: Passivate Surface Treatment: Inc Shelf Life: Iva Inc Shelf Life: Iva Int Of Measure: Iva Iva <	
Head Style: Heaxagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment: Passivate Surface Treatment: Inc Shelf Life: N/a Unc Shelf Life: N/a Unit Of Measure: Image: No Fig:	
Hexagon Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Stole comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material: 66 federal standard all material responses Strafee Treatment: Passivate Quep-35 federal specification: Cap-35 federal specification single treatment response Thread Series Designator: Iva Material: Na Material: Order Freatment Specification Iva Material Specification single treatment response Thread Series Designator: Iva Material: Iva Steff Life: N/a Entification: Iva Iva	
Haar Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Stel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Strafee Treatment: Passivate Quep-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: r Pomilitarization: Formation: No Pig:	-
Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification single treatment response Thread Series Designator: Inc Shelf Life: N/a Encil Stread Series Designator: Inc Shelf Life: N/a Encil Stread Series Designator: Inc Shelf Life: N/a Encil Stread Series Designator: Inc Shelf Life: N/a Encil Series Designator: Fig:	-
Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Quep-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unc Shelf Life: N/a Ensile Comp Fig:	-
Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Qu-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Instant0.375 inches0.375 inchesPeatures Provide:Finished headThready Qty Per Inch (tpi):16Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:66 federal standard all material responsesSurface Treatment:PassivateQrq-9.35 federal specification single treatment responseInceSheff Life:IvaIvaInti Of Measure:IvaFig:NoFig:	
0.375 inchesFeatures Provided:Finished headThready Qty Per Inch (tpi):16Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Bole comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:Bole comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:Bole comp 303 or steel comp 304 or steel comp 305 or steel comp 316PasivateBurface Treatment:PasivateCureat Specification single treatment responseParieral Specification single treatment responseDirterad Series Designator:Intre Specification single treatment responseParieralDirterad Series Designator:Intre Specification single treatment responseDirterad Series Designator:Intre Specification single treatment responseDirterad Series Designator:Intre Specification single treatment responseIntre Specification single treatment responseIntre Specification single treatment responseIntre Specification:Intre Specification:Intre Specification:Intre Specification:Intre Specification:Intre Specif	
Features Provided: Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: 8teel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	
Finished head Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Thready Qty Per Inch (tpi): 16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Features Provided:
16 Min. Tensile Strength (psi): 80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 64 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qap-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: - - Demilitarization: No	
Min. Tensile Strength (psi):80000 pounds per square inchMaterial:Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316Material Specification:66 federal standard all material responsesSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:-Demilitarization:FFDemilitarization:NoFig:	Thready Qty Per Inch (tpi):
80000 pounds per square inch Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Material Specification single treatment response Mread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Min. Tensile Strength (psi):
Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	80000 pounds per square inch
Material Specification: 66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:
66 federal standard all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material Specification:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Pemilitarization: No Fig:	66 federal standard all material responses
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment:
Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Passivate
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Surface Treatment Specification:
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No	Qq-p-35 federal specification single treatment response
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Unc
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A003b0	Fiig:
	A003b0