NSN 5305-00-281-6387

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-281-6387 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.562 inches **Fastener Length:** 0.625 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch Hardness Rating: 72.0 rockwell b **Primary Washer Outside Diameter:** Between 0.372 inches and 0.383 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.022 inches Material: Steel primary washer **Material Specification:** Mil-s-11310 military specification single material response fastener or astm a575 assn standard single material response fastener or astm a576 assn standard single material response fastener or astm a108 assn standard single material response fastener **Surface Treatment:** Cadmium **Thread Series Designator:**

N/a

Unc

Shelf Life:

NSN 5305-00-281-6387

Assembled Washer Screw - Page 2 of 2



		• -						
ш	ın	ıt (r 1t	ΝЛ	മാ	CI.	ire:	•

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-11310 spec.