## NSN 5305-00-281-6858



Thumbscrew - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-00-281-6858 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.783 inches and 0.905 inches **Fastener Length:** Between 0.845 inches and 0.905 inches **Head Style:** Wing no. 3 **Head Height:** Between 0.350 inches and 0.470 inches Width Between Flats: Between 0.780 inches and 0.900 inches **Point Style: Pointless Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Special Features:** With 0.060 in. Min 0.080 in. Maximum diameter hole drilled through one flat portion of head wing Material: Steel comp 1010 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1026 or steel comp 1035 or steel comp 1040 or steel comp 1042 or steel comp 1045 or steel comp 1046 or steel comp 1548 or steel comp 1049 or steel comp 1050 **Material Specification:** Astm a108 assn standard all material responses **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No Fiig:

A003b0

**Demilitarization:**