## NSN 5305-00-281-8876

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-281-8876 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 0.406 inches **Head Style:** Fillister extended washer **Head Diameter:** 0.312 inches **Head Height:** Between 0.082 inches and 0.092 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.023 inches and 0.028 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel **Screw Material Specification:** Qq-s-689, cond c4 /canceled/ federal specification single material response **Screw Surface Treatment:** Cadmium and zinc and chromate **Screw Surface Treatment Specification:** An-p-61 /canceled/ assn standard 1st treatment response and tt-p-1757, type 1 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-00-281-8876

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0