NSN 5305-00-281-9492

Machine Screw - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5305-00-281-9492

3a
Thread Direction:
Right-hand
Thread Length:
Between 0.427 inches and 0.510 inches
Fastener Length:
Between 0.490 inches and 0.510 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.590 inches and 0.622 inches
Head Height:
Between 0.302 inches and 0.322 inches
Hole Diameter:
0.070 inches
Internal Drive Style:
Slot
Thread Diameter:
0.375 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 16
16
16 Min. Tensile Strength (psi):
16 Min. Tensile Strength (psi): 125000 pounds per square inch
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round longitudinal hole
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round longitudinal hole Thread Series Designator:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round longitudinal hole Thread Series Designator: Unc

NSN 5305-00-281-9492

Machine Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A500d0