## NSN 5305-00-281-9498

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-281-9498 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.410 inches and 0.510 inches **Fastener Length:** Between 0.490 inches and 0.510 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.389 inches and 0.414 inches **Head Height:** Between 0.256 inches and 0.276 inches **Hole Diameter:** 0.070 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches **Hole Quantity:** 2 Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8740 **Screw Material Specification:** Ams 6322 assn standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unc

Shelf Life: N/a

## NSN 5305-00-281-9498

Machine Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A500d0