## NSN 5305-00-281-9782

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-281-9782

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.740 inches and 0.820 inches
Fastener Length:
Between 1.428 inches and 1.448 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.389 inches and 0.414 inches
Head Height:
Between 0.256 inches and 0.276 inches
Hole Diameter:
0.070 inches
Internal Drive Style:
Slot
End Application:
Spec item
Thread Diameter:
0.250 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Screw Material:
Steel comp 8740
Screw Material Specification:
Ams 6322 assn standard single material response
Screw Surface Treatment:
Cadmium
Screw Surface Treatment Specification:
Ams 2400 assn standard single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
I In a

Unc

## NSN 5305-00-281-9782

Machine Screw - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0