## NSN 5305-00-281-9784

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-281-9784

inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.636 inches and 0.698 inches
Fastener Length:
Between 0.678 inches and 0.698 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.292 inches and 0.313 inches
Head Height:
Between 0.209 inches and 0.229 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Hole Quantity:
2
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Min. Tensile Strength (psi):
32  Min. Tensile Strength (psi): 125000 pounds per square inch
32  Min. Tensile Strength (psi): 125000 pounds per square inch  Hardness Rating:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round Thread Series Designator:
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round Thread Series Designator: Unf

## NSN 5305-00-281-9784

Machine Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A500d0