NSN 5305-00-282-2026

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-282-2026 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.370 inches and 0.780 inches **Fastener Length:** Between 1.120 inches and 1.130 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.745 inches and 0.755 inches **Head Height:** Between 0.369 inches and 0.381 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project **Special Features:** Cone point 55 to 65 degrees of angle by 0.250 in.Lg by 0.159 in. Min, 0.175 in. Maximum dia Material: Copper alloy 360 **Material Specification:** Qq-b-626, 1/2 h federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification all treatment responses **Thread Series Designator:** Unc Shelf Life:

She N/a

NSN 5305-00-282-2026

Externally Relieved Body Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0