

View Online at <https://aerobasegroup.com/nsn/5305-00-282-4916>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.289 inches and 0.453 inches

Fastener Length:

Between 0.594 inches and 0.656 inches

Head Style:

Round extended washer

Head Diameter:

Between 0.427 inches and 0.447 inches

Head Height:

Between 0.096 inches and 0.106 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.028 inches and 0.033 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Screw Material:

Steel comp 8630 or steel comp 4037

Screw Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

Screw Surface Treatment:

Cadmium or zinc

Screw Surface Treatment Specification:

Qq-p-416 federal specification 1st treatment response or qq-z-325 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.