NSN 5305-00-282-6233

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-282-6233 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.345 inches and 0.484 inches **Fastener Length:** Between 1.391 inches and 1.438 inches **Head Style:** Round **Head Diameter:** Between 0.309 inches and 0.331 inches **Head Height:** Between 0.088 inches and 0.102 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Screw Material:** Steel comp 8630 **Screw Material Specification:** Mil-s-6050 military specification single material response or an-s-9 military standard single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig:

A500d0

NSN 5305-00-282-6233

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6050 spec.