## NSN 5305-00-282-6709

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-282-6709 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.344 inches and 0.375 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.165 inches and 0.180 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Screw Material:** Steel comp 430 or steel comp 302 **Screw Material Specification:** Qq-s-763, class 4 uns s43000 federal specification 1st material response or mil-s-7720, comp fm or g, uns s30200 military specification 2nd material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Supplementary Features:** Replace by nsn 5305-01-078-4451, p/n an50d10-6 **Thread Series Designator:** Unf **Specification Data:** 81348-ff-s-92 government specification and 88044-an501 rev 6 government standard **Specification Or Standard:** 1 type and 4s style Shelf Life:

Demilitarization:

**Unit Of Measure:** 

No

N/a

## NSN 5305-00-282-6709

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-7720 spec.