## NSN 5305-00-282-7676

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-282-7676 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.625 inches and 0.725 inches **Fastener Length:** 0.750 inches **Head Style:** Fillister **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.466 inches and 0.478 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.025 inches **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-00-282-7676

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0