

View Online at <https://aerobasegroup.com/nsn/5305-00-282-8681>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.806 inches and 1.000 inches

Fastener Length:

Between 1.781 inches and 1.828 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.036 inches and 1.145 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.562 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

Screw Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6758 spec.