## NSN 5305-00-282-9145

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-282-9145

Thread Class:						
3a						
Thread Direction:						
Right-hand						
Thread Length:						
Between 0.598 inches and 0.698 inches						
Fastener Length:						
Between 0.678 inches and 0.698 inches						
Head Style:						
Flat chamfer						
Head Diameter:						
Between 0.389 inches and 0.414 inches						
Head Height:						
Between 0.256 inches and 0.276 inches						
Hole Diameter:						
0.070 inches						
Internal Drive Style:						
Cross recess type 1						
Thread Diameter:						
0.250 inches						
Hole Quantity:						
2						
Thready Qty Per Inch (tpi):						
Thready Qty Per Inch (tpi):						
Thready Qty Per Inch (tpi): 20						
20						
20 Min. Tensile Strength (psi):						
20 Min. Tensile Strength (psi): 125000 pounds per square inch						
20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:						
20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c						
20 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material:						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification:						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment:						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification:						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style:						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round						
Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: Between 26.0 rockwell c and 32.0 rockwell c Screw Material: Steel comp 8740 Screw Material Specification: Ams 6322 assn standard single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: Ams 2400 assn standard single treatment response Head Hole Configuration Style: Round Thread Series Designator:						

## NSN 5305-00-282-9145

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A500d0