NSN 5305-00-282-9503

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-282-9503



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.430 inches and 0.578 inches Fastener Length: Between 0.891 inches and 0.938 inches **Head Style:** Round **Head Diameter:** Between 0.464 inches and 0.493 inches **Head Height:** Between 0.133 inches and 0.150 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Screw Material:

Steel comp 8630

Screw Material Specification:

Mil-s-6050 military specification single material response or an-s-9 military standard single material response

Screw Surface Treatment:

Cadmium

Screw Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

NSN 5305-00-282-9503

Machine Screw - Page 2 of 2

Mil-std (military Standard):

Mil-s-6050 spec.

