NSN 5305-00-282-9835

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-282-9835 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.312 inches **Fastener Length:** 0.375 inches **Head Style:** Fillister **Head Diameter:** Between 0.250 inches and 0.270 inches **Head Height:** Between 0.102 inches and 0.113 inches Washer Quantity: **Internal Drive Style:** Torque **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch Hardness Rating: 72.0 rockwell b **Primary Washer Outside Diameter:** Between 0.327 inches and 0.338 inches **Primary Washer Style:** Flat internal teeth **Primary Washer Material Thickness:** 0.020 inches Material: Steel comp 1010 or steel comp 1011 or steel comp 1015 or steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 **Material Specification:** Qq-s-633 federal specification all material responses **Surface Treatment:** Cadmium **Thread Series Designator:**

N/a

Unc

Shelf Life:

NSN 5305-00-282-9835

Assembled Washer Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0