NSN 5305-00-283-4583

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-283-4583 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.380 inches and 0.447 inches **Fastener Length:** Between 0.890 inches and 0.937 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.376 inches and 0.381 inches **Head Height:** 0.044 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.5 degrees and 100.5 degrees **Surface Finish:** 32.0 microinches threads **Special Features:** Furnished with one o-ring seal Material: Titanium alloy **Material Specification:** Nas621 comp 6al-4v assn standard single material response or ams4928 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-00-283-4583

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0