## NSN 5305-00-283-4586

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-283-4586

Thread C	lass:
3a	
Thread D	irection:
Right-han	
Thread Lo	-
Between (	0.443 inches and 0.510 inches
Fastener	Length:
Between (	0.828 inches and 0.875 inches
Head Sty	le:
Flat count	ersunk undercut
Head Dia	meter:
Between (	0.502 inches and 0.507 inches
Head Hei	ght:
Between (	0.071 inches and 0.073 inches
Grip Dian	neter:
Between (	0.2490 inches and 0.2495 inches
Internal D	Drive Style:
High-torqu	Je
Thread D	iameter:
0.250 inch	nes
Grip Leng	gth:
Between (	0.365 inches and 0.385 inches
Thready	Qty Per Inch (tpi):
28	
Counters	ink Angle:
Between 9	99.5 degrees and 100.5 degrees
Surface F	Finish:
32.0 micro	pinches threads
Special F	eatures:
Furnished	l with one o-ring seal
Material:	
Titanium a	alloy
Material S	Specification:
Nas621 c	omp 6al-4v assn standard single material response or ams4928 assn standard single material respons
Thread S	eries Designator:
Unjf	
Shelf Life	x:
N/a	
Unit Of M	leasure:
Demilitar	ization:
No	

## NSN 5305-00-283-4586

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

