NSN 5305-00-283-4590

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-283-4590 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 1.079 inches and 1.109 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4340

Surface Treatment:

Paint grip

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-283-4590

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0