

View Online at <https://aerobasegroup.com/nsn/5305-00-285-5263>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.361 inches and 0.480 inches

Fastener Length:

0.500 inches

Head Style:

Pan

Head Diameter:

Between 0.407 inches and 0.425 inches

Head Height:

Between 0.139 inches and 0.151 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.216 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.395 inches and 0.410 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.020 inches and 0.025 inches

Material:

Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer

Material Specification:

Sae assn standard all material responses primary washer

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0