

View Online at <https://aerobasegroup.com/nsn/5305-00-285-5263>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.361 inches and 0.480 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.407 inches and 0.425 inches

**Head Height:**

Between 0.139 inches and 0.151 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.216 inches

**Thready Qty Per Inch (tpi):**

24

**Hardness Rating:**

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.395 inches and 0.410 inches

**Primary Washer Style:**

Flat external teeth

**Primary Washer Material Thickness:**

Between 0.020 inches and 0.025 inches

**Material:**

Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer

**Material Specification:**

Sae assn standard all material responses primary washer

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0