Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-285-5274

2a Thread Direction: Right-hand Thread Length: 0.281 inches Fastener Length: Between 0.281 inches and 0.312 inches Head Style: Fillister Head Diameter: Between 0.286 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Vasher Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Qty Per Inch (tpi): 32	
Right-handThread Length:0.281 inchesFastener Length:Between 0.281 inches and 0.312 inchesHead Style:FillisterHead Diameter:Between 0.208 inches and 0.226 inchesHead Height:Between 0.086 inches and 0.096 inchesVasher Quantity:1Cross recess type 1Thread Diameter:0.138 inchesThready Lyper Inch (tpi):	
Thread Length: 0.281 inches Fastener Length: Between 0.281 inches and 0.312 inches Head Style: Fillister Head Diameter: Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Washer Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
0.281 inches Fastener Length: Between 0.281 inches and 0.312 inches Head Style: Fillister Head Diameter: Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Head Height: 1 fiternal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Ver Inch (tpi):	
Fastener Length:Between 0.281 inches and 0.312 inchesHead Style:FillisterHead Diameter:Between 0.208 inches and 0.226 inchesHead Height:Between 0.086 inches and 0.096 inchesWasher Quantity:1Internal Drive Style:Cross recess type 1Thread Diameter:0.138 inchesThready Europe Inch (tpi):	
Between 0.281 inches and 0.312 inches Head Style: Fillister Fillister Head Diameter: Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Vasher Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thread Y Per Inch (tpi):	
Head Style: Fillister Head Diameter: Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Head Height: Head Height:	
Filister Head Diameter: Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Washer Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Head Diameter: Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Washer Quantity: 1 1 Internal Drive Style: Cross recess type 1 Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Between 0.208 inches and 0.226 inches Head Height: Between 0.086 inches and 0.096 inches Washer Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Head Height: Between 0.086 inches and 0.096 inches Washer Quantity: 1 Internal Drive Style: Cross recess type 1 Cross recess type 1 Interad Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Between 0.086 inches and 0.096 inches Washer Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Washer Quantity: 1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
1 Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Cross recess type 1 Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
Thread Diameter: 0.138 inches Thready Qty Per Inch (tpi):	
0.138 inches Thready Qty Per Inch (tpi):	
Thready Qty Per Inch (tpi):	
32	
Hardness Rating:	
40.0 rockwell c primary washer and 50.0 rockwell c primary washer	
Primary Washer Outside Diameter:	
Between 0.218 inches and 0.231 inches	
Primary Washer Style:	
Split helical ring	
Primary Washer Material Thickness:	
0.031 inches	
Surface Treatment:	
Cadmium or zinc	
Surface Treatment Specification:	
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2n	nd treatment response
Thread Series Designator:	
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization: No	

NSN 5305-00-285-5274

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

