Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-285-5275



2a Thread Direction:

Thread Class:

Right-hand

Thread Length:

Between 0.341 inches and 0.477 inches

Fastener Length:

0.500 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.473 inches and 0.492 inches

Head Height:

Between 0.130 inches and 0.144 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.494 inches and 0.510 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.023 inches and 0.028 inches

Material Specification:

Sae assn standard all material responses primary washer

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-00-285-5275

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

