**Thread Class:** 

**Right-hand** 

**Thread Direction:** 

2a

Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-285-5276



## **Thread Length:** Between 0.194 inches and 0.292 inches Fastener Length: Between 0.281 inches and 0.312 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.099 inches and 0.110 inches Washer Quantity: 1 **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 40.0 rockwell c primary washer and 50.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.365 inches and 0.381 inches **Primary Washer Style:** Flat external teeth **Primary Washer Material Thickness:** Between 0.020 inches and 0.025 inches **Material Specification:** Sae assn standard all material responses primary washer Surface Treatment: Cadmium or zinc Surface Treatment Specification: Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:**

Unf

Shelf Life:

N/a

- Unit Of Measure:
- ---

## NSN 5305-00-285-5276

Assembled Washer Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

