

View Online at <https://aerobasegroup.com/nsn/5305-00-285-5277>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.507 inches and 0.605 inches

Fastener Length:

0.625 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.099 inches and 0.110 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.365 inches and 0.381 inches

Primary Washer Style:

Flat external teeth

Primary Washer Material Thickness:

Between 0.020 inches and 0.025 inches

Material:

Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary washer or steel comp 1561 primary washer or steel comp 1566 primary washer

Material Specification:

Sae assn standard all material responses primary washer

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0