NSN 5305-00-285-5277

Assembled Washer Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-00-285-5277 |
|--|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.507 inches and 0.605 inches |
| Fastener Length: |
| 0.625 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.357 inches and 0.373 inches |
| Head Height: |
| Between 0.099 inches and 0.110 inches |
| Washer Quantity: |
| 1 |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Hardness Rating: |
| 40.0 rockwell c primary washer and 50.0 rockwell c primary washer |
| Primary Washer Outside Diameter: |
| Between 0.365 inches and 0.381 inches |
| Primary Washer Style: |
| Flat external teeth |
| Primary Washer Material Thickness: |
| Between 0.020 inches and 0.025 inches |
| Material: |
| Steel comp 1050 primary washer or steel comp 1551 primary washer or steel comp 1552 primary washer or steel comp 1053 primary washer |
| or steel comp 1054 primary washer or steel comp 1055 primary washer or steel comp 1059 primary washer or steel comp 1060 primary |
| washer or steel comp 1561 primary washer or steel comp 1566 primary washer |
| Material Specification: |
| Sae assn standard all material responses primary washer |
| Surface Treatment: |
| Cadmium or zinc |
| Surface Treatment Specification: |
| Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response |
| Thread Series Designator: |
| Unf |

N/a

Shelf Life:

NSN 5305-00-285-5277

Assembled Washer Screw - Page 2 of 2



| | | • - | | | | | | |
|---|-----|-----|----|-----|----|----|----|----|
| | In | | Of | RЛ | മാ | CI | ır | Δ. |
| L | ,,, | | | IVI | ca | | | |

--

Demilitarization:

No

Fiig:

A003b0