NSN 5305-00-285-5282



Assembled Washer Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-285-5282 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.282 inches and 0.344 inches **Fastener Length:** Between 0.344 inches and 0.375 inches **Head Style:** Round **Head Diameter:** Between 0.287 inches and 0.309 inches **Head Height:** Between 0.107 inches and 0.120 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Primary Washer Outside Diameter:** Between 0.305 inches and 0.319 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.031 inches Material: Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener **Material Specification:** 66 federal standard all material responses primary washer **Surface Treatment:** Cadmium and chromate **Thread Series Designator:** Unc Shelf Life: N/a

Demilitarization: No

Unit Of Measure:

NSN 5305-00-285-5282

Assembled Washer Screw - Page 2 of 2



Fiig:

A003b0