Assembled Washer Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-00-285-5283



Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.407 inches and 0.469 inches

Fastener Length:

Between 0.469 inches and 0.500 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.306 inches and 0.322 inches

Head Height:

Between 0.085 inches and 0.096 inches

Washer Quantity:

1

Internal Drive Style:

Slot

Thread Diameter:

0.164 inches

Thready Qty Per Inch (tpi):

32

Primary Washer Outside Diameter:

Between 0.305 inches and 0.319 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.031 inches

Material:

Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener

Material Specification:

66 federal standard all material responses primary washer

Surface Treatment:

Dichromate zinc

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-00-285-5283

Assembled Washer Screw - Page 2 of 2

Fiig: A003b0

