NSN 5305-00-285-5284

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-285-5284 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.156 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Round **Head Diameter:** Between 0.334 inches and 0.359 inches **Head Height:** Between 0.123 inches and 0.137 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 45.0 rockwell c primary washer and 53.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.359 inches and 0.373 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.047 inches Material: Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener **Material Specification:** Sae assn standard single material response primary washer **Surface Treatment:**

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response or qq-z-325, type 2, class 3 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

NSN 5305-00-285-5284

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0