

View Online at <https://aerobasegroup.com/nsn/5305-00-285-5285>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.350 inches

**Fastener Length:**

0.438 inches

**Head Style:**

Fillister

**Head Diameter:**

Between 0.292 inches and 0.313 inches

**Head Height:**

Between 0.118 inches and 0.130 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

45.0 rockwell c primary washer and 53.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.283 inches and 0.297 inches

**Primary Washer Style:**

Split helical ring

**Primary Washer Material Thickness:**

0.040 inches

**Material:**

Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener

**Material Specification:**

Sae assn standard single material response primary washer

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0