NSN 5305-00-285-5287

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-285-5287
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.216 inches and 0.352 inches
Fastener Length:
0.375 inches
Head Style:
Pan
Head Diameter:
Between 0.473 inches and 0.492 inches
Head Height:
Between 0.162 inches and 0.175 inches
Washer Quantity:
1
internal Drive Style:
Cross recess type 1
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
20
Hardness Rating:
40.0 rockwell c primary washer and 50.0 rockwell c primary washer
Primary Washer Outside Diameter:
Between 0.494 inches and 0.510 inches
Primary Washer Style:
Flat external teeth
Primary Washer Material Thickness:
Between 0.023 inches and 0.028 inches
Material:
Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 101
or steel comp 1019 or steel comp 1020 or steel comp 1050 or steel comp 1551 or steel comp 1552 or steel comp 1053 or steel comp
1055 or steel comp 1060 or steel comp 1561 or steel comp 1566
Material Specification:
Sae assn standard all material responses
Surface Treatment:
Cadmium or zinc
Surface Treatment Specification:
Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series Designator:
Jnc

N/a

Shelf Life:

NSN 5305-00-285-5287

Assembled Washer Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0