

View Online at <https://aerobasegroup.com/nsn/5305-00-285-5295>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.478 inches

**Fastener Length:**

0.500 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Washer Quantity:**

1

**Internal Drive Style:**

Cross recess type 1

**End Application:**

Nsn 2320-01-318-9902 het (heavy equipment transporter); nsn 4210-01-486-1035 tactical fire fighting truck (tfft)

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

40.0 rockwell c primary washer and 50.0 rockwell c primary washer

**Primary Washer Outside Diameter:**

Between 0.372 inches and 0.383 inches

**Primary Washer Style:**

Flat internal teeth

**Primary Washer Material Thickness:**

0.022 inches

**Special Features:**

Nha nsn 2510-01-354-4365 right side door; tm 9-2320-360-24p fig 201

**Material:**

Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1017 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener

**Surface Treatment:**

Cadmium or zinc

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0