## NSN 5305-00-286-1666

Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-00-286-1666 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.484 inches and 0.516 inches **Head Style:** Round **Head Diameter:** Between 0.146 inches and 0.162 inches **Head Height:** Between 0.059 inches and 0.069 inches **First Diameter From Head:** 0.064 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.234 inches and 0.266 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 **Surface Treatment:** Cadmium and zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:**