NSN 5305-00-286-1699

Externally Relieved Body Screw - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5305-00-286-1699 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.219 inches and 0.281 inches |
| Fastener Length: |
| Between 0.297 inches and 0.328 inches |
| Head Style: |
| Fillister |
| Head Diameter: |
| Between 0.422 inches and 0.453 inches |
| Head Height: |
| Between 0.109 inches and 0.141 inches |
| First Diameter From Head: |
| 0.123 inches |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.047 inches and 0.078 inches |
| Internal Drive Style: |
| Cross recess type 1 |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 36 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Astm a582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0