NSN 5305-00-288-2431

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-288-2431
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.646 inches and 0.696 inches
Fastener Length:
Between 2.328 inches and 2.358 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.633 inches
Shoulder Diameter:
0.327 inches first shoulder and 0.328 inches first shoulder
Shoulder Length:
1.662 inches first shoulder and 1.682 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp
4130
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nac1705 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-00-288-2431

Shoulder Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0