# NSN 5305-00-290-2458

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-290-2458 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 0.500 inches **Head Style:** Round **Head Diameter:** Between 0.287 inches and 0.309 inches **Head Height:** Between 0.107 inches and 0.120 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel **Screw Material Specification:** 

Qq-s-633-canc federal specification single material response or qq-w-409 military specification single material response

### **Screw Surface Treatment:**

Cadmium and chromate or zinc

#### **Screw Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification 1st treatment response and qq-p-416, type 2, cl 3 federal specification 2nd treatment response or qq-z-325, type 2, cl 3 federal specification 3rd treatment response

## **Thread Series Designator:**

Unc

#### **Specification Or Standard:**

1 type and 1s style

#### **Shelf Life:**

N/a

**Unit Of Measure:** 

--

### Demilitarization:

No

#### Fiig:

A500d0

# NSN 5305-00-290-2458

Machine Screw - Page 2 of 2



Mil-std (military Standard):

spec.