NSN 5305-00-292-6473

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-292-6473 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.417 inches **Fastener Length:** 0.500 inches **Head Style:** Fillister **Head Diameter:** Between 0.292 inches and 0.313 inches **Head Height:** Between 0.118 inches and 0.130 inches Washer Quantity: **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 **Hardness Rating:** 45.0 rockwell c primary washer and 53.0 rockwell c primary washer **Primary Washer Outside Diameter:** Between 0.283 inches and 0.297 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** 0.040 inches Material: Steel comp 1060 primary washer **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unc

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-00-292-6473

Assembled Washer Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0