

View Online at <https://aerobasegroup.com/nsn/5305-00-292-6485>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.210 inches

Fastener Length:

Between 0.219 inches and 0.250 inches

Head Style:

Fillister

Head Diameter:

Between 0.292 inches and 0.313 inches

Head Height:

Between 0.118 inches and 0.130 inches

Washer Quantity:

1

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

35.0 rockwell c primary washer and 53.0 rockwell c primary washer

Primary Washer Outside Diameter:

Between 0.283 inches and 0.297 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

0.040 inches

Material:

Steel comp 1010 fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener or steel comp 1018 fastener or steel comp 1019 fastener or steel comp 1020 fastener

Material Specification:

Sae assn standard single material response primary washer

Surface Treatment:

Cadmium or zinc

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0