Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-292-6485

2a	
Thread Directior	:
Right-hand	
Thread Length:	
0.210 inches	
Fastener Length	
Between 0.219 in	ches and 0.250 inches
Head Style:	
Fillister	
Head Diameter:	
Between 0.292 in	ches and 0.313 inches
Head Height:	
Between 0.118 in	ches and 0.130 inches
Washer Quantity	:
1	
Internal Drive St	yle:
Cross recess type	1
Thread Diameter	:
0.190 inches	
Thready Qty Per	Inch (tpi):
32	
Hardness Rating	
35.0 rockwell c p	rimary washer and 53.0 rockwell c primary washer
Primary Washer	Outside Diameter:
Between 0.283 in	ches and 0.297 inches
Primary Washer	Style:
Split helical ring	
Primary Washer	Material Thickness:
0.040 inches	
Material:	
Steel comp 1010	fastener or steel comp 1011 fastener or steel comp 1013 fastener or steel comp 1015 fastener or steel comp 1016 fastener
	8 fastener or steel comp 1019 fastener or steel comp 1020 fastener
Material Specific	
	d single material response primary washer
Surface Treatme	
Cadmium or zinc	
Surface Treatme	nt Specification:
	, cl 3 federal specification 1st treatment response or qq-z-325, type 1, cl 3 federal specification 2nd treatment response
Thread Series D	
Unf	-
Shelf Life:	
-	

NSN 5305-00-292-6485

Assembled Washer Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0