NSN 5305-00-292-8791

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-292-8791 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.329 inches and 0.422 inches **Fastener Length:** Between 0.797 inches and 0.828 inches **Head Style:** Hexagon **Head Height:** 0.250 inches Width Between Flats: Between 0.422 inches and 0.453 inches **First Diameter From Head:** Between 0.310 inches and 0.311 inches **Second Diameter From Head:** 0.188 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.328 inches and 0.359 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.406 inches and 0.468 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 1117 **Material Specification:** Qq-s-637 federal specification single material response **Surface Treatment:** Chromate zinc **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-00-292-8791

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0