## NSN 5305-00-297-2527

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-297-2527 **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** 0.625 inches **Head Style:** Hexagon countersunk undercut **Bottom Countersink Diameter:** 0.391 inches **Head Height:** 0.375 inches Width Between Flats: 0.435 inches Point Style: Flat **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.312 inches **Nonstandard Thread Pitch Diameter:** +0.2830/+0.2849 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** 100.0 degrees Material: Steel comp 8740 **Material Specification:** ponse

| material Specification.                     |
|---|
| Ams 6322 assn standard single material resp |
| Thread Series Designator:                   |
| Uns   |
| Shelf Life:                                 |
| N/a   |
| Unit Of Measure:                            |
|   |
| Demilitarization:                           |
| No  |
|   |
|   |

## NSN 5305-00-297-2527

Setscrew - Page 2 of 2



Fiig:

A003b0