## NSN 5305-00-297-7608

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-297-7608

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.344 inches
Fastener Length:
Between 1.641 inches and 1.687 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.287 inches and 0.334 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 26.0 rockwell c and 32.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Steel comp 4037 or steel comp 8630
Screw Material Specification:
Ams 6300 assn standard 1st material response or mil-s-6050 military specification 2nd material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 cl 3 federal specification single treatment response
Thread Series Designator:
Unc
Specification Data:
80205-nas517 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5305-00-297-7608

Machine Screw - Page 2 of 2



Fiig:

A500d0

Mil-std (military Standard):

Mil-s-6050 spec.