## NSN 5305-00-297-7639

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-297-7639 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.200 inches and 0.250 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Oval countersunk **Head Diameter:** Between 0.195 inches and 0.225 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Head Surface Treatment:** Paint **Screw Surface Treatment:** Enamel **Thread Series Designator:** Unc **Specification Or Standard:** 1 type and 6s style **Departure From Cited Designator:** As modified by yield strength Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## **NSN 5305-00-297-7639** Machine Screw - Page 2 of 2



Fiig:

A500d0