## NSN 5305-00-297-7743

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-00-297-7743 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.103 inches and 0.145 inches **Fastener Length:** Between 0.114 inches and 0.145 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.195 inches and 0.225 inches **Head Height:** Between 0.038 inches and 0.047 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 48 Min. Tensile Strength (psi): 55000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Copper alloy **Screw Material Specification:** Qq-b-613 federal specification single material response or qq-b-626 federal specification single material response or qq-w-321 federal specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416 type 2 class 3 federal specification single treatment response **Thread Series Designator:** Unf **Specification Or Standard:** 1 type and 2s style **Departure From Cited Designator:** 

N/a

**Unit Of Measure:** 

Shelf Life:

As modified by fastener length

## NSN 5305-00-297-7743

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0