NSN 5305-00-297-8236



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-00-297-8236 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.495 inches and 0.562 inches **Fastener Length:** Between 0.531 inches and 0.562 inches **Head Style:** Fillister **Head Diameter:** Between 0.124 inches and 0.140 inches **Head Height:** Between 0.055 inches and 0.062 inches **Hole Diameter:** 0.031 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.086 inches **Hole Quantity:** Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 303se or steel comp 304 or steel comp 316 **Screw Material Specification:** 66 federal standard all material responses **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Head Hole Configuration Style:** Round **Thread Series Designator:** Unc **Specification Or Standard:**

Shelf Life:

N/a

1 type and 5s style

NSN 5305-00-297-8236

Machine Screw - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A500d0